




ヘキサロビュラ穴付きねじ仕様表

— タッピンねじ（樹脂用）（なべ頭） —



■代表品番：HLPP ■材質：鋼（三価クロメート）

d	2	2.2	2.5	3	3.5	4	
d_k	3.6	4	4.2	5.6	6.9	7.5	
k	1.5	1.4	1.6	2.1	2.3	2.6	
t_{\min}	0.6	0.6	0.7	1	1.1	1.3	
t_{\max}	0.8	0.8	0.9	1.3	1.4	1.7	
工具*	X06BIP	X06BIP	X08BIP	X10BIP	X15BIP	X20BIP	
l	5	HLPP2005	HLPP2205				
	6	HLPP2006	HLPP2206	HLPP2506	HLPP3006		
	8	HLPP2008	HLPP2208	HLPP2508	HLPP3008	HLPP3508	HLPP4008
	10	HLPP2010	HLPP2210	HLPP2510	HLPP3010	HLPP3510	HLPP4010
	12		HLPP2212	HLPP2512	HLPP3012	HLPP3512	HLPP4012
	16		HLPP2216	HLPP2516	HLPP3016	HLPP3516	HLPP4016
	20					HLPP3520	HLPP4020
	25					HLPP3525	HLPP4025
	30					HLPP3530	HLPP4030

* 通常のヘキサロビュラ穴用工具（代表品番：X(B)、X(L)）ではなく、トルク伝達率がより大きいヘキサロビュラ穴（IP）用工具（代表品番：X(BIP)）に適合しています。